


SPEC SHEET

PCNF6X30-36R (Cooler No Floor)

Walk-In Cooler

EXTERIOR W x L x H 6'-7" x 29'-6" x 7'-3"	INTERIOR W x L x H 5'-11" x 28'-10" x 6'-11"	FLOOR · VOLUME 171 sq ft · 1,180 cu ft	INSULATION 4" PU, R28 / R33	DOORS 36"x77" RH
---	--	--	---------------------------------------	----------------------------



GENERAL SPECIFICATIONS


PANELS: 4" thick foamed-in-place polyurethane insulation, cam-lock panels, tongue & groove design, aluminum finish, CFC and HFC free materials, 10 year panel warranty and 1 year parts warranty.

FLOOR: No floor. Walls are set on the existing floor in metal U-channel (2" side legs, 4" wide).

DOOR: 36"x77", right hinged. Self-closing, spring loaded hinge, flush-mounted, keyed locking door handle, 120V/1P/1A heater wire, 120V vapor proof light fixture provided loose (bulb not included).

APPROVALS: NSF/ANSI 7 Commercial Refrigerators and Freezers, UL723 Flame Spread and Smoke Development (Flame Spread Index 5, Smoke Developed Index 300), Department of Energy (DOE) Compliance and Certified, ASTM Test 518, ASTM Test E84.



LAYOUT



DOOR DETAIL · SIDE SECTION

Door: 36" x 77", Right Hinge

Side Section (Clear Height)



CUSTOMER APPROVAL

Name: _____

Signature: _____

Date: _____