


SPEC SHEET

PCWF5X20-36R (Cooler With Floor) Walk-In Cooler

EXTERIOR W x L x H 4'-11" x 19'-8" x 7'-7"	INTERIOR W x L x H 4'-3" x 19' x 6'-11"	FLOOR · VOLUME 81 sq ft · 562 cu ft	INSULATION 4" PU, R28 / R33	DOORS 36"x77" RH
--	---	---	---------------------------------------	----------------------------



GENERAL SPECIFICATIONS


PANELS: 4" thick foamed-in-place polyurethane insulation, cam-lock panels, tongue & groove design, aluminum finish, CFC and HFC free materials, 10 year panel warranty and 1 year parts warranty.

FLOOR: Diamond plate floor, suitable for hand-truck and pallet jack operation.

DOOR: 36"x77", right hinged. Self-closing, spring loaded hinge, flush-mounted, keyed locking door handle, 120V/1P/1A heater wire, 120V vapor proof light fixture provided loose (bulb not included).

APPROVALS: NSF/ANSI 7 Commercial Refrigerators and Freezers, UL723 Flame Spread and Smoke Development (Flame Spread Index 5, Smoke Developed Index 300), Department of Energy (DOE) Compliance and Certified, ASTM Test 518, ASTM Test E84.



LAYOUT



DOOR DETAIL · SIDE SECTION

Door: 36" x 77", Right Hinge

Side Section (Clear Height)



CUSTOMER APPROVAL

Name: _____

Signature: _____

Date: _____