


## SPEC SHEET

### PFWF12X30-36R (Freezer With Floor)

#### Walk-In Freezer

| EXTERIOR W x L x H      | INTERIOR W x L x H         | FLOOR · VOLUME          | INSULATION       | DOORS      |
|-------------------------|----------------------------|-------------------------|------------------|------------|
| 11'-6" x 29'-6" x 7'-7" | 10'-10" x 28'-10" x 6'-11" | 313 sq ft · 2,164 cu ft | 4" PU, R28 / R33 | 36"x77" RH |



#### GENERAL SPECIFICATIONS


**PANELS:** 4" thick foamed-in-place polyurethane insulation, cam-lock panels, tongue & groove design, aluminum finish, CFC and HFC free materials, 10 year panel warranty and 1 year parts warranty.

**FLOOR:** Diamond plate floor, suitable for hand-truck and pallet jack operation.

**DOOR:** 36"x77", right hinged. Self-closing, spring loaded hinge, flush-mounted, keyed locking door handle, 120V/1P/1A heater wire, pressure relief vent for freezer, 120V vapor proof light fixture provided loose (bulb not included).

**APPROVALS:** NSF/ANSI 7 Commercial Refrigerators and Freezers, UL723 Flame Spread and Smoke Development (Flame Spread Index 5, Smoke Developed Index 300), Department of Energy (DOE) Compliance and Certified, ASTM Test 518, ASTM Test E84.



#### LAYOUT



#### DOOR DETAIL · SIDE SECTION

Door: 36" x 77", Right Hinge

Side Section (Clear Height)



#### CUSTOMER APPROVAL

Name: \_\_\_\_\_

Signature: \_\_\_\_\_

Date: \_\_\_\_\_